

ODE-3-210105-1042-01

Optidrive E3 Single Phase VFD Datasheet

0,55 kW (0,75 HP), 10,5 A, 110-115 V, 1P

Variadores de frecuencia



Input Ratings

Supply Voltage	110-115 V
Input Phases	1
Supply Current Continuous	12,5 A
Supply Fuse or MCB (Type B)	16 A

Output Ratings

Motor Output Rating	0,55 kW (0,75 HP)
Output Voltage	0 – Supply Voltage
Output Current	10,5 A

Cable Information

Max Supply Cable Size	8 mm ² (0,01 sq in)
Max Motor Cable Size	8 mm ² (0,01 sq in)
Max Motor Cable Length	100 m (328 ft)

Factory Build Options

EMC Filter	Sin filtro CEM interno
Brake Transistor	Transistor de freno
Enclosure	IP20
Display	
PCB Coating	

Dimensions

Size	2
Height	221 mm (8,7 in)
Width	110 mm (4,33 in)
Depth	150 mm (5,91 in)
Weight	1,7 kg (3,75 lbs)
Fixings	4 x M5

Packaged Dimensions

Height	234 mm (9,21 in)
Width	144 mm (5,67 in)
Depth	260 mm (10,24 in)
Weight	1,93 kg (4,25 lbs)



 **Buy this drive or get more information**
Find your local sales partner on
inverterkdrives.com

